

Specifications

Models	GR-26J	
Measurements	US	Metric
Working height*	31 ft 11 in	9.90 m
Platform height	25 ft 11 in	7.90 m
Horizontal reach maximum**	8 ft 3 in	2.51 m
Up-and-over clearance maximum	21 ft 10 in	6.70 m
A Platform length	2 ft 5 in	0.75 m
B Platform width	2 ft 11 in	0.90 m
Toeboard height	6 in	0.15 m
C Height - stowed	6 ft 6 in	1.99 m
D Length - stowed	9 ft 3 in	2.8 m
E Width	3 ft 3 in	0.99 m
F Wheelbase	3 ft 11 in	1.20 m
G Ground clearance - center	3.4 in	8.5 cm

Productivity

Maximum platform occupancy (indoor/outdoor)***	2/1	2/1
Lift capacity	440 lbs	200 kg
Vertical jib rotation	140° (+70°/-70°)	
Turntable rotation	350° non-continuous	
Turntable tailswing	3.8 in	95 mm
Drive speed - stowed	2.8 mph	4.5 km/h
Drive speed - raised	0.4 mph	0.65 km/h
Gradeability****	25%	
Turning radius - inside	23.5 in	0.6 m
Turning radius - outside	82.3 in	2.09 m
Controls	24V DC proportional	
Drive	dual rear wheel	
Disc brakes	dual rear wheel	
Tires (solid non-marking)	16-5-11 ¼	40.5 cm diam.

Power

Power source	24 V DC (twelve 2V batteries, 250 Ah capacity)	
Hydraulic system capacity	4.84 gal	22 L



Weight*****

5,843 lbs 2,650 kg

Standards Compliance

ANSI A92.20, CSA B354.4

Range Of Motion GR-26J



* The US equivalent of working height adds 6 ft to platform height.

** Non-working reach

*** ANSI/CSA maximum occupancy is 2 indoor and outdoor.

**** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.

***** Weight will vary depending on options and/or country standards.

Features

Standard Features

Measurements

GR-26J

- 31 ft 10 in (9.90 m) working height
- 8 ft 3 in (2.51 m) horizontal reach
- 21 ft 10.5 in up-and-over reach
- Up to 440 lbs (200 kg) lift capacity
- 4 ft 10 in (1.45 m) jib boom with 140° working range

Productivity

- Standard steel platform 2 ft 11 in x 2 ft 5.5 in (0.90 m x 0.75 m) with sliding midrail
- Hydraulic turntable rotation
- Fully proportional lift and drive system
- Drivable at full height
- Low 6 in (15 cm) platform entry height
- Rigid steel tube in hydraulic mast
- 3 ft 3 in (0.99 m) compact width
- Low unit height of 6 ft 6 in (1.99 m)
- Low machine weight of 5,843 lbs (2,650 kg)
- Onboard diagnostic system
- AC power to platform
- Direct electric rear wheel drive with electric parking brake
- Front wheel steering
- Brake release switch
- Reinforced ABS chassis covers
- Two tie down attachment points at overhead crane point
- Non-marking solid tires
- Drive enable system
- Horn
- Hour meter
- Tilt level sensor with audible alarm
- Platform overload sensing
- Manual platform lowering valve
- Emergency stop at both platform and ground controls
- Motion alarm
- Flashing beacon
- Fork pockets

Standard Features

Power

- Automatic 30 Amp 24 V battery onboard charger
- 24 V DC (twelve 2V batteries, 250 Ah capacity)
- Battery charge indicator



Genie United States

6464 185th Ave. NE
Redmond, WA 98052
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By:

Effective Date: August, 2020. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie and AWP are registered trademarks of Terex Corporation or its subsidiaries. © 2020 Terex Corporation.